

Parameters

| | Item | DH-WJ0510 | DH-WJ1010 |
|----|--------------------|----------------------|------------------------|
| 1 | System | Dyhua WJ system | Dyhua WJ system |
| 2 | Driver mode | Servo motor + lead | Servo motor + lead scr |
| 3 | Cutting speed | 18000mm/min for | 18000mm/min for 7mm |
| 4 | Working table | 500mm*1000mm | 1000mm*1000 |
| 5 | Cutting thickness | Max to 40mm(option | Max to 40mm(option f |
| 6 | Position tolerance | ±0.08mm | ±0.08mm |
| 7 | Repeat tolerance | ±0.01mm | ±0.01mm |
| 8 | File Format | DXF,CFF2,NC | DXF,CFF2,NC |
| 9 | Water flow | > 1L/minute | > 1L/minute |
| 10 | Power | 7.5KW(pump),< | 7.5KW(pump),< |
| 11 | Weight | 1000KG(pump),680K | 1000KG(pump),680K |
| 12 | Power supply | Three phase 380V +/- | Three phase 380 |
| 13 | Air pressure | >0.6MPA | >0.6MPA |
| 14 | Total power | 9KW | 9KW |

| |
|----------------------|
| |
| |
| ew |
| n thickness |
| mm |
| or other |
| |
| |
| |
| |
| |
| $\bar{J}(\text{mac}$ |
| V +/- |
| |
| |